

EXTOX UNI i-12

GAS MONITORING CONTROLLER

TECHNICAL DATA SHEET



- * 12 channel controller
- * Wide variety of accept detectors
- * 4 programmable alarm levels
- * LCD display with backlight
- * Data /event logging
- * Mutable audible alarm output
- * Up to 32 pcs. programmable output relay
- * Parallel signal processing safety system
- * Needed maintenance warning

FEATURES

<u>Type:</u>	EXTOX-UNI i-12
<u>Supply:</u>	210-242V 50Hz 200 VA,
<u>Ingress protection:</u>	IP54 {MSZ IEC 529}
<u>Ambient temperature:</u>	0 – +40°C
<u>Class of indirect contact protection:</u>	I.
<u>Operated transmitter:</u>	E-TD-S1 {semiconductor} E-TD-P1 {catalytic} E-MC-E1 {electrochemical} E-MC-NE1 {electrochemical} IRTA {infrared} ECO-CO-2 {electrochemical}

Loadability of control relay outputs:

- * 250V 50Hz 5A 1250VA
- * 30V DC 5A

Acoustic and light signal output loadability: 1A / output

Mechanical dimensions: 500x500x250mm

Weight: 19 kg



MŰSZER AUTOMATIKA KFT.
H-2040 Budaörs, Komáromi utca 22. Hungary

telephone: +36 23 365-280, Fax: +36 23 365-837
web: www.gazerzekele.hu
e-mail: gaz@muszerautomatika.hu

